

Annual Drinking Water Quality Report for 2019

Town of Schaghticoke

290 Northline Road, Schaghticoke, NY 12121

(Public Water Supply Identification Number WD#1 NY4100046, WD#2 NY4100048 and WD#3 NY4100062)

INTRODUCTION

To comply with State regulations, the Town of Schaghticoke, will be annually issuing a report describing the quality of your drinking water. The purpose of this report is to raise your understanding of drinking water and awareness of the need to protect our drinking water sources. We are very pleased to provide you with this year's Annual Water Quality Report. The purpose of this report is to raise your understanding of drinking water and awareness of the need to protect our drinking water sources. Last year, we conducted tests for over 80 contaminants. We detected 1 of those contaminants at a level higher than the State allows in the 4th quarter. As we told you at the time, our water temporarily exceeded a drinking water standard and we modified our treatment process to rectify this problem. This report is an overview of last year's water quality. Included are details about where your water comes from, what it contains, and how it compares to New York State standards. Our constant goal is and always has been, to provide to you a safe and dependable supply of drinking water. We want you to understand the efforts we make to continually improve the water treatment process and to protect our water resources. If you have any questions concerning this report or concerning your drinking water please contact: *Mr. Shawn M. Cross, Operator in Responsible Charge (ORC), 290 Northline Drive, Melrose, NY 12121, Telephone (518) 753-9982 or (518) 461-3350.* We want our valued customers to be informed about their water service. If you want to learn more, please attend any of our regularly scheduled Town Board meetings. They are held on the 2nd Wednesday of each month, 7:00 PM at the *Town Hall, 290 Northline Road; Telephone (518) 753-6915.* If you want to learn more, please call us.

WHERE DOES OUR WATER COME FROM?

The Town of Schaghticoke purchases all of its water. Water District (WD) #2 purchases its water from the City of Mechanicville. The City of Mechanicville operates a surface water filtration plant. Two reservoirs feed this system: The Mechanicville Reservoir, which is the primary source and a small downstream terminal reservoir. The Mechanicville Water Treatment Plant is a U.S. Filter Modular Aquarius (AQ-300B) which consists of flocculation, clarification and filtration for water treatment. The plant is automatically controlled and packaged in (3) steel tanks producing 2,100 gallons/minute. The treatment process consists of coagulation using polyaluminum chloride to cause small particles to stick together when the water is mixed forming larger heavier particles. Sedimentation allows the newly formed larger particles to settle out naturally in inclined tube settlers. The mixed media filter bed consists of anthracite coal, silica sand and garnet sand which removes smaller particles by trapping them in the spaces between the sand grains. Also used in the treatment process is sodium permanganate which is used for taste and odor control, color reduction and iron and manganese oxidation. The filtered water from the treatment unit is fed into the clearwell. The water is then pumped out of the clearwell and chlorinated with liquid sodium hypochlorite. At this point the water flows into two (2) chlorine contact tanks. They are circular; epoxy coated steel bolted steel and concrete tanks with interior baffling and a storage capacity of 250,000 gallons each. The baffling in the tank provides increased detention time and adequate time for the water to be disinfected by the chlorine.

Consolidated Water District #1 (formerly Water Districts 1, 4, 4B, 5 and 6) and Water District #3 purchase water from the City of Troy. We receive water that has been treated at the Troy Water Treatment Plant (TWTP). The City of Troy draws its water from a surface water supply; the spring fed Tomhannock Reservoir. It is located to the northeast of the City of Troy. Water flows from the Tomhannock Reservoir to the TWTP, a complete treatment facility. In an effort to lower the formation of disinfection byproducts (DBBPs), TWTP has started to add potassium permanganate at the Tomhannock Reservoir. Potassium permanganate is a strong oxidant that is used to oxidize iron and manganese, but does not produce the DBBPs that chlorine does. Potassium permanganate is being fed seasonally from mid June to about September or October depending on the iron and manganese levels in the raw water. Additionally chlorine dioxide is added at Melrose Station to oxidize the organic material that leads to the formation of disinfection byproducts when it reacts with chlorine but unlike chlorine, chlorine dioxide does not form DBBPs like THM's or HAA5's. Chlorine dioxide is fed year-round. Like Mechanicville, Troy has the same water treatment processes and additionally they add fluoride at low levels to protect teeth against dental cavities.

Additionally, liquid sodium hypochlorite is injected at the Melrose Pump Station, before being pumped to the Storage Facility. Sodium hypochlorite solution used to prevent the possibility of bacterial contamination. This is added so that an adequate chlorine residual is maintained throughout the distribution system north of Grants Hollow. This is fed year-round and monitored daily.

In WD#1 we have two storage tanks. The Speigletown Tank is 180,000-gallon reinforced concrete structure consisting of 2 separate storage compartments of 90,000 gallons each. At present daily usage, this capacity would support 2.5 to 3 days of usage, pending no emergency usage. The tank is located off Fogarty Road on the hilltop overlooking

Speigletown. A chain-link fence at the site plus gates at the highway leading to the tank site secure the tank itself. The Melrose Tank is a steel cylindrical 140,000-gallon tank located on a hill, east of the intersection of Valley Falls Road and Route 40. It provides a 3-day supply barring any emergency use, based on present usage.

In general, the sources of drinking water (both tap water and bottled water) include rivers, lakes, streams, ponds, reservoirs, springs and wells. As water travels over the surface of the land or through the ground, it dissolves naturally-occurring minerals and in some cases, radioactive material, and can pick up substances resulting from the presence of animals or from human activities. Contaminants that may be present in source water include microbial contaminants; inorganic contaminants; pesticides and herbicides; organic chemical contaminants; and radioactive contaminants. In order to ensure that tap water is safe to drink, the State and EPA prescribe regulations, which limit the amount of certain contaminants in water, provided by public water systems. The State Health Department's and the FDA's regulations establish limits for contaminants in bottled water which must provide the same protection for public health.

FACTS AND FIGURES

Consolidated Water District #1 provides water through 1,219 service connections to a population of approximately 2,848 persons. The total amount of water purchased for WD#1 was 84,620,844 gallons and the amount delivered was 68,363,905 gallons with a loss of 16,256,939 gallons 19.2 % or unaccounted water in 2019. Unaccounted or non-revenue producing water can be attributed to water usage for fire protection, flushing water main breaks and leaks. Our water system's average daily demand is approximately 242,230 gallons our single highest day was 393,090 gallons. The annual charge per one thousand gallons of water delivered is \$4.60 per 1000 gallons for Consolidated WD #1. Water District #2 provides water through 188 service connections to a population of approximately 564 persons. The annual charge for water is \$6.11 per 1000 gallons. Water District #3 provides water through 366 service connections to a population of approximately 1,098 persons. The annual charge per one thousand gallons of water delivered is \$4.60 per 1000 gallons.

ARE THERE CONTAMINANTS IN OUR DRINKING WATER?

In accordance with State regulations, the Town of Schaghticoke routinely monitors your drinking water for numerous contaminants. We test your drinking water for inorganic contaminants, radiological contaminants, lead and copper, nitrate, volatile organic contaminants, and synthetic organic contaminants. In addition, we test 3 samples for coliform bacteria every month from the Consolidated Water District. The table presented below depicts which contaminants were detected in your drinking water. The state allows us to monitor for certain contaminants less than once per year because the concentrations of these contaminants are not expected to vary significantly from year to year. Some of the data, though representative of the water quality, is more than one year old and is noted.

It should be noted that all drinking water, including bottled drinking water, may be reasonably expected to contain at least small amounts of some contaminants. The presence of contaminants does not necessarily pose a health risk. More information about contaminants and potential health effects can be obtained by calling the EPA's Safe Drinking Water Hotline (800-426-4791) or the Rensselaer County Department of Health (518) 270-2626.

WHAT DOES THIS INFORMATION MEAN?

As you can see from the Table on page 6, we exceeded the MCL for the Trihalomethanes for Water District #1 and are required to furnish the following information:

We have learned through our monitoring and testing that some constituents have been detected; however, these compounds were detected below New York State requirements. MCL's are set at very stringent levels. To understand the possible health effects described for many regulated contaminants, a person would have to drink 2 liters of water every day at the MCL level for a lifetime to have a one-in-a-million chance of having the described health effect.

Under the LT2 (Long Term Enhanced Surface Water Treatment Rule, small surface water or GUIDI systems could monitor for E. coli biweekly for 1 year instead of performing more costly Cryptosporidium/Giardia testing to determine treatment requirements for their water sources. The City of Mechanicville performed this monitoring on their Upper & Lower Reservoirs from 10/2/17 through 9/17/18. An average E. coli concentration greater than 100/100 ml of sample would trigger Cryptosporidium and Giardia monitoring for 24 months. The average for the Lower Reservoir was 264 E. coli/100 ml and this triggered Cryptosporidium/Giardia monitoring which commenced in September 2018.

Information on Cryptosporidium

Cryptosporidium is a microbial pathogen found in surface water and groundwater under the influence of surface water. Although filtration removes Cryptosporidium, the most commonly used filtration methods cannot guarantee 100 percent removal. During September 2018 through December 2019, as part of our sampling plan, Lower Reservoir source water samples were collected and analyzed for Cryptosporidium

ooocysts. Six sample of the 16 samples collected was presumed positive for Cryptosporidium, and was confirmed positive. Therefore, our monitoring indicates the presence of Cryptosporidium in our source water. Current test methods do not allow us to determine if the organisms are dead or if they are capable of causing disease. 10 additional source water samples did not show the presence of Cryptosporidium. Ingestion of Cryptosporidium may cause cryptosporidiosis, a gastrointestinal infection. Symptoms of infection include nausea, diarrhea, and abdominal cramps. Most healthy individuals can overcome disease within a few weeks. However, immuno-compromised people are at greater risk of developing life-threatening illness. We encourage immuno-compromised individuals to consult their health care provider regarding appropriate precautions to take to avoid infection.

Information on Giardia

Giardia is a microbial pathogen present in varying concentrations in many surface waters and groundwater under the influence of surface water. Giardia is removed/inactivated through a combination of filtration and disinfection or by disinfection. During September 2018 through December 2019, as part of our sampling plan, four samples of our Lower Reservoir source water samples were collected and analyzed for Giardia cysts. Of these samples 13 of the 16 samples were confirmed positive for Giardia cysts. Therefore, our monitoring indicates the presence of Giardia in our source water. Current test methods do not allow us to determine if the organisms are dead or if they are capable of causing disease. Ingestion of Giardia may cause giardiasis, an intestinal illness. People exposed to Giardia may experience mild or severe diarrhea, or in some instances no symptoms at all. Fever is rarely present. Occasionally, some individuals will have chronic diarrhea over several weeks or a month, with significant weight loss. Giardiasis can be treated with anti-parasitic medication. Individuals with weakened immune systems should consult with their health care providers about what steps would best reduce their risks of becoming infected with Giardiasis. Individuals who think that they may have been exposed to Giardiasis should contact their health care providers immediately. The Giardia parasite is passed in the feces of an infected person or animal and may contaminate water or food. Person to person transmission may also occur in day care centers of other settings where handwashing practices are poor.

IS OUR WATER SYSTEM MEETING OTHER RULES THAT GOVERN OPERATIONS?

During 2019, our system was in compliance with applicable State drinking water reporting, monitoring and operating requirements.

Results of regular monitoring are an indicator of whether or not your drinking water meets health standards. During 2019, Mechanicville did not sample for the inorganics and secondary inorganics. They were issued a notice of violation for not completing this testing.

DO I NEED TO TAKE SPECIAL PRECAUTIONS?

Although our drinking water met or exceeded state and federal regulations, some people may be more vulnerable to disease causing microorganisms or pathogens in drinking water than the general population. Immuno-compromised persons such as persons with cancer undergoing chemotherapy, persons who have undergone organ transplants, people with HIV/AIDS or other immune system disorders, some elderly, and infants can be particularly at risk from infections. These people should seek advice from their health care provider about their drinking water. EPA/CDC guidelines on appropriate means to lessen the risk of infection by Cryptosporidium, Giardia and other microbiological pathogens are available from the Safe Drinking Water Hotline (800-426-4791).

INFORMATION ON FLUORIDE ADDITION

Our system is one of many drinking water systems in New York State that provides drinking water with a controlled, low level of fluoride for consumer dental health protection. Fluoride is added to your water if you are in Consolidated Water District #1. Fluoride is added to the water we purchase, by the City of Troy before it is delivered to us. According to the United States Centers for Disease Control, fluoride is very effective in preventing cavities when present in drinking water at a controlled level. To ensure that the fluoride supplement in your water provides optimal dental protection, the City of Troy monitors fluoride levels on a daily basis to make sure fluoride is maintained at a target level of 1.0 mg/l. During 2019 monitoring showed that fluoride levels in your water were within 0.2 mg/l of the target level 100 % of the time. None of the monitoring showed fluoride at levels that approach the 2.2 mg/l MCL for fluoride.

INFORMATION ON LEAD

If present, elevated levels of lead can cause serious health problems, especially for pregnant women and young children. Lead in drinking water is primarily from materials and components associated with service lines and home plumbing. The Town of Schaghticoke is responsible for providing high quality drinking water, but cannot control the variety of materials used in plumbing components. When your water has been sitting for several hours, you can minimize the potential for lead exposure by flushing your tap for 30 seconds to 2 minutes before using water for drinking or cooking. If you are concerned about lead in your water, you may wish to have your water tested.

Information on lead in drinking water, testing methods, and steps you can take to minimize exposure is available from the Safe Drinking Water Hotline or at <http://www.epa.gov/safewater/lead>

WHAT IS THE SOURCE WATER ASSESSMENT PROGRAM (SWAP)?

To emphasize the protection of surface and ground water sources used for public drinking water, Congress amended the Safe Drinking Water Act (SDWA) in 1996. The amendments require that New York State Department of Health's Bureau of Public Water Supply Protection is responsible for ensuring that source water assessments are completed for all of New York's public water systems.

A source water assessment provides information on the potential contaminant threats to public drinking water sources:

- ◆ each source water assessment will: determine where water used for public drinking water comes from (delineate the source areas)
- ◆ Inventory potential sources of contamination that may impact public drinking water sources
- ◆ Assess the likelihood of a source water area becoming potential contaminated

The SWAP summaries for the City of Troy and City of Mechanicville are attached to the end of this report.

WATER CONSERVATION TIPS

The Town of Schaghticoke encourages water conservation. There are a lot of things you can do to conserve water in your own home. Conservation tips include:

- Only run the dishwasher and clothes washer when there is a full load
- Use water saving showerheads
- Install faucet aerators in the kitchen and the bathroom to reduce the flow from 4 to 2.5 gallons per minute
- Water gardens and lawn for only a couple of hours after sunset

CAPITAL IMPROVEMENTS

There were no major projects completed in 2019 although some water main, valves and hydrants were repaired or replaced. There are no improvements planned for Consolidated Water District #1 in 2020.

CLOSING

Thank you for allowing us to continue providing your family with clean, quality water this year. In order to maintain a safe and dependable water supply we sometimes need to make improvements that will benefit our customers. We ask that all our customers help us protect our water sources, which are the heart of our community. Please call our office if you have questions.

SCHAGHTICOKE WATER DISTRICT #2 TABLE OF DETECTED CONTAMINANTS						
Public Water Supply Identification Number NY4100048						
Water purchased from the City of Mechanicville						
Contaminant	Violation Y/N	Level Detected	Unit Measurement	MCLG	MCL	Likely Source of Contamination
Microbiological Contaminants						
Turbidity (highest turbidity sample from 8/14/19)	Y	0.14 ¹	NTU	N/A	TT=1.0 NTU	Soil runoff
		100%			TT=95% samples < 0.3	
Inorganic Contaminants (samples from 8/27/18 unless otherwise noted)						
Arsenic	N	2.5	ppb	N/A	10	Erosion of natural deposits
Barium	N	35.5	ppb	2000	2000	Naturally occurring
Chloride	N	29.3	ppm	N/A	250	Naturally occurring or indicative of road salt contamination.
Copper Schaghticoke WD#2 (samples from 8/6/19-8/27/19)	N	0.33 ²	ppm	1.3	AL=1.3	Corrosion of household plumbing systems; erosion of natural deposits; leaching from wood preservatives
Range of copper concentrations		0.07-0.40				
Lead Schaghticoke WD#2 (samples from 8/6/19-8/27/19)	N	4 ³	ppb	0	AL=15	Corrosion of household plumbing systems, erosion of natural deposits
Range of lead concentrations		1-5				
Manganese 1/17/19-10/1/19 (average) range	N	13.2	ppb	N/A	300	Naturally occurring
		5.6-21.1				
Nickel	N	0.68	ppb	N/A	N/A	Erosion of natural deposits
Odor	N	1.0	units	N/A	3	Natural sources
pH	N	7.81	units		6.5-8.5	
Sodium ⁴	N	17.7	ppm	N/A	N/A	Geology; Road Salt
Sulfate	N	24.2	ppm	N/A	250	Geology
Disinfection Byproducts (Quarterly samples from 2/13/19, 5/14/19, 8/13/19, & 11/13/19)						
Stage 2 Haloacetic Acids (HAA5)(Average)	N	45 ⁵	ppb	N/A	60	By-product of drinking water chlorination
Weaver Petroleum						
Range of values for HAA5		17-44				

Stage 2 Haloacetic Acids (HAA5)(Average) Hemstead Park Range of values for HAA5		32.4 8.6-35.8				
Stage 2 TTHM[Total Trihalomethanes](Average) ⁵ Weaver Petroleum Range of values for TTHM	N	64.9 ⁵ 40.3-67.6	ppb	0	80	By-product of drinking water chlorination
Stage 2 TTHM[Total Trihalomethanes](Average) ⁵ Hemstad Park Range of values for TTHM		66.9 47.8-95.6				
Chlorine Residual (average) range	N	1.21 0.76-2.13	ppm	MRDLG N/A	MRDL 4	Used in the treatment and disinfection of drinking water
Total Organic Carbon⁶(monthly samples from 2019)						
Total Organic Carbon Monthly Compliance Ratio	N	1.27-2.53	N/A	Compliance ratio >=1	TT	Organic material both natural and man made; Organic pollutants, decaying vegetation.
Notes:						
1. Turbidity is a measure of the cloudiness of the water. We monitor it because it is a good indicator of the effectiveness of our filtration system. Level detected represents the highest level detected. Distribution system turbidity performed 5 times a week with 1.16 NTU being highest level detected and 0.28 NTU being the average level detected.						
2. The level presented represents the 90 th percentile of 5 test sites. The level included in the table represents the average of the two highest levels detected. The action level for copper was not exceeded at any of the 5 sites tested.						
3. The level presented represents the 90 th percentile of 5 test sites. The level included in the table represents the average of the two highest levels detected. The action level for lead was exceeded at any of the 5 sites tested.						
4. Water containing more than 20 mg/l should not be consumed by persons on severely restricted sodium diets.						
5. The average is based on a Locational Running Annual Average (LRAA). The averages shown are the highest LRAAs for each of the 2 sites monitored in of 2019. The highest LRAA for the THMs was in the 4 th quarter. The highest LRAA for Hemstead Park was in the 3 rd quarter and Weaver Petroleum was in the 2 nd quarter.						
6. The Interim Enhanced Surface Water Treatment Rule (IESWTR) requires monitoring of raw and finished water Total Organic Carbon (TOC). Depending on the raw water alkalinity value, proper water treatment should remove between 15% to 50% of the raw water TOC thus reducing the amount of disinfection byproducts produced.						

SCHAGHTICOKE CONSOLIDATED WATER DISTRICT #1 TABLE OF DETECTED CONTAMINANTS							
Public Water Supply Identification Number NY4100046 and NY4100062							
Water Purchased from City of Troy PWD ID NY4100050							
Contaminant	Violation Yes/No	Date of Sample	Level Detected	Unit Measurement	MCLG	Regulatory Limit (MCL, TT or AL)	Likely source of Contamination
Inorganic Contaminants							
Copper WD#3 Range of values	N	8/9/19- 8/13/19	0.08 ¹ ND-0.16	ppm	1.3	AL=1.3	Corrosion of household plumbing systems; erosion of natural deposits; leaching from wood preservatives
Copper WD#1 Range of values	N	8/6/19- 8/9/19	90 ¹ 0.01-0.19				
Lead WD#3 Range of values	N	8/9/19- 8/13/19	3 ² ND-4	ppb	15	AL=15	Corrosion of household plumbing systems; erosion of natural deposits;
Lead WD#1 Range of values	N	8/6/19- 8/9/19	9 ² ND-7				
Barium	N	7/3/19	27.9	ppb	2000	2000	Naturally occurring
Chloride	N	7/3/19	25.8	ppm	N/A	250	Naturally occurring, road salt
Color (avg) range	N	Daily	0 ND-2	units	N/A	15	Naturally occurring
Turbidity (avg) range	N	Daily	0.38 0.11-1.40	NTU	N/A	5	Soil runoff
Fluoride (avg) range	N	Daily	0.77 0.17-1.11	ppm	N/A	2200	Additive for strong teeth and prevention of dental carries
Iron (avg) range	N	Weekdays	20 ND-50	ppb	N/A	300	Naturally occurring
Manganese (avg) range	N	Weekdays	1 ND-40	ppb	N/A	300	Naturally occurring
pH (avg) range	N	Daily	8.44 6.38-9.02	units	N/A	6.5-8.5	
Sodium ³	N	7/3/19	12.7	ppm	N/A	N/A	Naturally occurring, road salt
Sulfate	N	7/3/19	20.2	ppm	N/A	250	Naturally occurring
Microbiological Contaminants							
Turbidity (Highest Value) ⁴		7/18/19	1.4 100%	NTU		TT=1.0 NTU TT= 95% samples < 0.3	Soil runoff
Radiological Contaminants							
Gross Beta Particles	N	3/11/16	0.681	pCi/l	0	4.0	Naturally occurring
Radium 226	N	3/11/16	0.456	pCi/l	0	5.0	Naturally occurring
Total Uranium	N	3/11/16	167	ppb	0	30.0	Naturally occurring
Disinfection Byproducts							
Stage 2 Haloacetic Acids (HAA5) WD#1 (average) Melrose Pumpouse Range of values	N	2/13/19 5/14/19 8/13/19 11/13/19	18.8 ⁵ 11.2-23	ppb	N/A	60	By-product of drinking water chlorination

Stage 2 Haloacetic Acids (HAA5) WD#1 (average) Speigletown Pump Station Range of values	N	2/13/19 5/14/19 8/13/19 11/13/19	40.1 ⁵ 28-50.5				
Stage 2 Haloacetic Acids (HAA5) WD#3 (average) 100 New Turnpike Range of values	N	2/13/19 5/14/19 8/13/19 11/13/19	35.8 ⁶ 27-45.9				
Stage 2 Haloacetic Acids (HAA5) WD#3 (average) 174 New Turnpike Range of values	N	2/13/19 5/14/19 8/13/19 11/13/19	20 ⁶ 15.7-26.8				
Stage 2 THM[Trihalomethanes] (average)WD#1 Melrose Pumphouse Range of values	N	2/13/19 5/14/19 8/13/19 11/13/19	56.7 ⁵ 24.7-83.3	ppb	0	80	By-product of drinking water disinfection
Stage 2 THM[Trihalomethanes] (average)WD#1 Speigletown Pump Station Range of values	N	2/13/19 5/14/19 8/13/19 11/13/19	44 ⁵ 18.3-72				
Stage 2 THM[Trihalomethanes] (average)WD#3 100 New Turnpike Range of values	N	2/13/19 5/14/19 8/13/19 11/13/19	43.4 ⁶ 18.5-71.2				
Stage 2 THM[Trihalomethanes] (average)WD#3 174 New Turnpike Range of values	N	2/13/19 5/14/19 8/13/19 11/13/19	48.6 ⁶ 30.2-72.9				
Chlorine Dioxide (avg) range	N	Daily	0.013 ND-0.19	ppm	0.8	0.8	Disinfectant
Chlorite (avg) range	N	Monthly	0.90 0.066-1.18	ppm	N/A	1.00	Byproduct chlorine dioxide treatment of water
Chlorate (avg) range	N	Monthly	0.83 0.53-1.06	ppm	N/A	N/A	Byproduct chlorine dioxide treatment of water
Chlorine Residual (average) Schaghticoke range	N	Daily	0.62 0.03-2.20	ppm	MRDL G N/A	MRDL 4	Used in the treatment and disinfection of drinking water
Notes: 1. During 2019 we collected and analyzed 10 samples for copper. The level included in the table represents the 90 th percentile of the 10 sites tested. The action level for copper was not exceeded at any of the sites tested. 2. During 2019 we collected and analyzed 10 samples for lead. The level included in the table represents the 90 th percentile of the 10 sites tested. The action level for lead was not exceeded at any of the sites tested. 3. Water containing more than 20 mg/l should not be consumed by persons on severely restricted sodium diets. 4. Turbidity is a measure of the cloudiness of the water. We monitor it because it is a good indicator of the effectiveness of our filtration system. Level detected represents the highest level detected. 5. The average is based on a Locational Running annual average. The average shown is the highest LRAA measured for each of the 2 sites in WD#1. The highest TTHM LRAAs was in the 4 th quarter of 2019. The highest HAA5 LRAAs for WD#1 was in the 3 rd quarter for Melrose and 4 th quarter for Speigletown. 6. The average is based on a Locational Running annual average. The average shown is the highest LRAA measured for each of the 2 sites in WD#3. The highest TTHM LRAAs was in the 4 th quarter of 2019. The highest HAA5 LRAAs for WD#3 was in the 3 rd quarter for 100 New Turnpike and 4 th quarter for 174 New Turnpike.							

Glossary

Non-Detects (ND) - laboratory analysis indicates that the constituent is not present.

Parts per million (ppm) or Milligrams per liter (mg/l) - one part per million corresponds to one minute in two years or a single penny in \$10,000.

Parts per billion (ppb) or Micrograms per liter - one part per billion corresponds to one minute in 2,000 years, or a single penny in \$10,000,000.

Picocuries per liter (pCi/L) - picocuries per liter is a measure of the radioactivity in water.

Nephelometric Turbidity Unit (NTU) - nephelometric turbidity unit is a measure of the clarity of water. Turbidity in excess of 5 NTU is just noticeable to the average person.

90th Percentile Value- The values reported for lead and copper represent the 90th percentile. A percentile is a value on a scale of 100 that indicates the percent of a distribution that is equal to or below it. The 90th percentile is equal to or greater than 90% of the lead and copper values detected at your water system.

Action Level - the concentration of a contaminant, which, if exceeded, triggers treatment, or other requirements, which a water system must follow.

Treatment Technique (TT) - A treatment technique is a required process intended to reduce the level of a contaminant in drinking water.

Maximum Contaminant Level - The "Maximum Allowed" (MCL) is the highest level of a contaminant that is allowed in drinking water. MCLs are set as close to the MCLGs as feasible using the best available treatment technology.

Maximum Contaminant Level Goal The "Goal" (MCLG) is the level of a contaminant in drinking water below which there is no known or expected risk to health. MCLGs allow for a margin of safety.

Locational Running Annual Average (LRAA): The LRAA is calculated by taking the average of the four most recent samples collected at each individual site

N/A-Not applicable

**City of Troy
Tomhannock Reservoir
Source Water Assessment Summary**

The NYS DOH has completed a Source Water Assessment for the Tomhannock Reservoir. The assessment is summarized below. The assessment includes a susceptibility rating based on the risk posed by each potential source of contamination and how likely contaminants could enter the reservoir(s). The susceptibility rating is an estimate of the potential for contamination. It does not mean that the water delivered to your home is or will become unsafe to drink. See section "Are there contaminants in our drinking water?" of this report, for information concerning low levels of contaminants in your water.

The assessment found the amount of pasture in the assessment area results in a potential for protozoa contamination. There is also possible contamination susceptibility associated with landfills in the assessment area. It should be noted that hydrologic characteristics (e.g. basin shape and flushing rates) generally make reservoirs sensitive to existing and new sources of phosphorus and microbial contamination.

Troy's water treatment plant performs multi level treatment to insure that Troy and Schaghticoke residents receive safe drinking water. Additionally, as this annual report shows your water is routinely monitored for a great number of potential contaminants.

A copy of the full Source Water Assessments, including a map of the assessment area, is available for review by contacting us at the number provided in this report.

**City of Mechanicville
PWSID NY4500166
Source Water Assessment Summary**

The NYS DOH has evaluated this Public Water System's (PWS) susceptibility to contamination under the Source Water Assessment Program (SWAP), and their findings are summarized in the paragraph below. It is important to stress that these assessments were created using available information and only estimate the potential for source water contamination. Elevated susceptibility ratings do not mean that source water contamination has or will occur for this PWS. This PWS provides treatment and regular monitoring to ensure the water delivered to consumers meets all applicable standards.

This assessment found an elevated susceptibility to contamination for this source of drinking water. The amount of agricultural lands in the assessment area results in elevated potential for protozoa and pesticides contamination. However, there is reason to believe that land cover data may over estimate the percentage of pasture in the assessment area. No permitted discharges are found in the assessment area.

There are no noteworthy contamination threats associated with other discrete contaminant sources. Finally, it should be noted that hydrologic characteristics (e.g. basin shape and flushing rates) generally make reservoirs highly sensitive to existing and new sources of phosphorus and microbial contamination.

A copy of the full Source Water Assessments, including a map of the assessment area, is available for review by contacting us at the number provided in this report.